

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 product identifier**

Product code : WZ61489F03
 Product name : NITROBASE WZ61 RHODAMINE TONER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Printing ink or Additive
 Uses advised against : Not applicable.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Distributor : Flint Ink (UK) Ltd
 Vauxhall Industrial Estate, Ruabon
 GB Wrexham
 LL14 6HU
 UNITED KINGDOM

e-mail address of person responsible for this SDS : compliancecentre@flintgrp.com

1.4 Emergency telephone number (with hours of operation)

+44 (0) 1978 823456 (8:00 h - 17:00 h)

History

Date of printing : 01.10.2011.
 Date of issue/ Date of revision : 29.09.2011.
 Date of previous issue : No previous validation.
 Version : 3

2. HAZARDS IDENTIFICATION**Classification and labeling according to Regulation (EC) 1907/2006 (REACH)**

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

2.1b Classification of the substance or mixture

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : F; R11
 Physical/chemical hazards : Highly flammable.
 Human health hazards : Not applicable.
 Environmental hazards : Not applicable.

2.2b Label elements

Hazard symbol or symbols :



Highly flammable

Risk phrases : R11- Highly flammable.

Safety phrases : S9- Keep container in a well-ventilated place.
 S16- Keep away from sources of ignition - No smoking.
 S33- Take precautionary measures against static discharges.
 S43- In case of fire, use dry chemical powder.
 S60- This material and its container must be disposed of as hazardous waste.

Contains :

2.3 Other hazards which do not result in classification

Results of PBT and vPvB assessment: See sections 12 for details.

NITROBASE WZ61 RHODAMINE TONER**2. HAZARDS IDENTIFICATION**

Contains nitrocellulose. Dry deposits of nitrocellulose inks are highly flammable.

3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures**

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name	%	REACH Registration number	CAS number	EC number	Classification
ethanol	50-75		64-17-5	200-578-6	F; R11 [2]
Pigment Red 81:5	2.5-25		63022-06-0	263-793-4	N; R50/53 [1]
ethyl acetate	1-5		141-78-6	205-500-4	F; R11 [1] Xi; R36 [2] R66, R67
xanthene lacquer (C.I. p.r. 81:2)	0.25-2.5		75627-12-2		N; R50/53 [1]

See section 16 for the full text of the R-phrases declared above

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

Hazardous ingredients / Classification according to Regulation (EC) 1272/2008 (CLP)

Chemical name	CAS number	Hazard statements	Classification
ethanol Pigment Red 81:5	64-17-5 63022-06-0	Highly flammable liquid and vapor. Very toxic to aquatic life with long lasting effects.	FLAMMABLE LIQUIDS - Category 2 AQUATIC TOXICITY (ACUTE) - Category 1 AQUATIC TOXICITY (CHRONIC) - Category 1
ethyl acetate	141-78-6	Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking.	FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects] - Category 3
xanthene lacquer (C.I. p.r. 81:2)	75627-12-2	Very toxic to aquatic life with long lasting effects.	AQUATIC TOXICITY (ACUTE) - Category 1 AQUATIC TOXICITY (CHRONIC) - Category 1

4. FIRST AID MEASURES**4.1 Description of first aid measures**

- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention/advice.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Give nothing by mouth. Do NOT induce vomiting.

Use suitable protective equipment (section 8).

NITROBASE WZ61 RHODAMINE TONER

4. FIRST AID MEASURES

4.2 Most important symptoms and effects, both acute and delayed

See toxicological information (section 11)

4.3 Indication of any immediate medical attention and special treatment needed

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media : Recommended:, alcohol-resistant foam, CO₂, powders, water spray

Extinguishing media not to be used : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for fire-fighters

Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area.

Avoid breathing vapor or spray. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and materials for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see section 8). Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with all local, regional, national and international regulations.

Store in a dry, cool and well-ventilated area, away from incompatible materials (see section 10).

Observe label precautions. Keep container tightly closed and in a well-ventilated place.

Keep away from sources of ignition - No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Storage temperature: 5 to 35°C

7.3 Specific end use(s)

Not applicable.

NITROBASE WZ61 RHODAMINE TONER

7. HANDLING AND STORAGE

7.4 Additional information

Contains nitrocellulose. Dry deposits of nitrocellulose inks are highly flammable. The product should not be applied on the same press as inks that generate heat during drying (for instance, two-pack inks, drying vegetable oil and alkyd-based inks), unless the press and exhaust ducting are completely cleaned between each product change. To avoid the risk of fire, do not allow this product to dry out. Do not mix with other wastes. Please consult the CEPE guideline for the safe use of cellulose nitrate printing inks and related products.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Ingredient name	Occupational exposure limits
ethanol	EH40/2005 WELs (United Kingdom (UK), 8/2007). TWA: 1920 mg/m ³ 8 hour(s). TWA: 1000 ppm 8 hour(s).
ethyl acetate	EH40/2005 WELs (United Kingdom (UK), 8/2007). STEL: 400 ppm 15 minute(s). TWA: 200 ppm 8 hour(s).

Other Exposure limits : CMR: See toxicological information (section 11)

8.2 Exposure controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

Individual protection measures

- Respiratory system** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
- Skin and body** : Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.
- Hands** : The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : For prolonged or repeated handling, use the following type of gloves:

May be used: neoprene
Not recommended: nitrile rubber, PVC
Recommended: fluor rubber, foil, butyl rubber
- Eyes** : Use safety eyewear designed to protect against splash of liquids.

Environmental exposure controls

Do not allow to enter drains or watercourses.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Violet.
- Odor** : Alcohol-like.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : >= 78 °C
- Flash point** : Closed cup: 12°C [theoretical]
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not applicable.
- Burning time** : Not applicable.

NITROBASE WZ61 RHODAMINE TONER**9. PHYSICAL AND CHEMICAL PROPERTIES**

Burning rate	: Not applicable.
Explosion limits	
Lower:	: 3 %Vol
Upper:	: 15 %Vol
Vapor pressure	: <= 78.7 hPa
Vapor density	: Not available.
Density	: ~ 1 g/cm ³
Solubility	: insoluble in water.
Octanol/water partition coefficient	: Not available.
Auto-ignition temperature	: ca 399 °C
Decomposition temperature	: Not available.
Viscosity	: Kinematic (20°C (68°F)): >4 cm ² /s (>400 cSt) Kinematic (40°C (104°F)): >0.07 cm ² /s (>7 cSt)
Explosive properties	: Not available.
Oxidizing properties	: Not available.

9.2 Other information

SADT : Not available.

10. STABILITY AND REACTIVITY**10.1 Reactivity**

Not available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Contains nitrocellulose. Dry deposits of nitrocellulose inks are highly flammable.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5 Incompatible materials

Keep away from the following materials to prevent strong exothermic reactions:
oxidizing agents, strong alkalis, strong acids

10.6 Hazardous decomposition products

Decomposition products may include the following materials:
carbon monoxide, carbon dioxide, smoke, oxides of nitrogen, amines

11. TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects**

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Ingestion may cause gastrointestinal irritation and diarrhea. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Substances / Mixtures

Acute toxicity :

NITROBASE WZ61 RHODAMINE TONER

11. TOXICOLOGICAL INFORMATION

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor LD50 Oral	Rat Rat	124700 mg/m3 7 g/kg	4 hours -
ethyl acetate	LD50 Oral	Rat	5620 mg/kg	-

Irritation/Corrosion : Not available.

Sensitization : Not available.

Mutagenicity : Not available.

Carcinogenicity : Not available.

Reproductive toxicity : Not available.

Specific target organ toxicity (single exposure) : Not available.

Specific target organ toxicity (repeated exposure) : Not available.

Aspiration hazard : Not available.

Chronic toxicity : Not available.

Teratogenicity : Not available.

Other information

Toxicokinetics

Absorption : Not available.

Distribution : Contains material which causes damage to the following organs: eye, lens or cornea.
Contains material which may cause damage to the following organs: blood, kidneys, the reproductive system, liver, upper respiratory tract, skin, central nervous system (CNS).

Metabolism : Not available.

Elimination : Not available.

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment but contains a substance or substances dangerous for the environment. See section 3 for details.

12.1 Toxicity data

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 2000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 ug/L Marine water	Crustaceans - Artemia franchiscana - LARVAE	48 hours
ethyl acetate	Acute LC50 42000 ug/L Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC <6.3 g/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1600000 ug/L Fresh water	Crustaceans - Asellus aquaticus	48 hours
	Acute LC50 154000 ug/L Fresh water	Daphnia - Daphnia cucullata - 11 days	48 hours
	Acute LC50 212500 ug/L Fresh water	Fish - Heteropneustes fossilis - 14.16 cm - 25.54 g	96 hours
Ink with Xanthene Dye	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute EC50 >100 mg/l	Fish	63 hours
	Acute IC50 >100 mg/l	Algae	72 hours

12.2 Persistence/degradability

Not available.

12.3 Bioaccumulative potential

Not available.

NITROBASE WZ61 RHODAMINE TONER

12. ECOLOGICAL INFORMATION

12.4 Mobility in soil

Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects

AOX : Not available.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

Do not mix with other wastes.

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European waste catalogue (EWC) : The European Waste Catalogue classification of this product, when disposed of as waste, is: 08 03 12* waste ink containing dangerous substances. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

Hazardous waste : Yes.

14. TRANSPORT INFORMATION

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

International transport regulations

14.1 UN number : UN1210

14.2 Proper shipping name : PRINTING INK

14.3 Transport hazard class(es) : 3



14.4 Packing group : II

14.5 Environmental hazards : Not applicable.

14.6 Special precautions for user : Not applicable.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Additional information

ADR ADN/ADNR

Classification code : F1

Special provisions : 163 640D

Hazard identification number : 33

ADR Tunnel Code: : (D/E)

Limited quantity : 5 L

IMDG

NITROBASE WZ61 RHODAMINE TONER

14. TRANSPORT INFORMATION

Emergency schedules (EmS) : F-E, S-D

Marine pollutant : Yes.

Limited quantity : 5 l

IATA		Max. Qty	Packaging instruction
Passenger and Cargo Aircraft	:	5 L	364
Cargo Aircraft Only	:	60 L	353
Limited quantity	:	1 L	Y341

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations : The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

See sections 2 and 3 for details.

VOC content : ~ 68 % ~ 679.9 g/L

Europe inventory : All components are listed or exempted.

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

16. OTHER INFORMATION

CEPE MSDS Code : 1

Full text of R-phrases referred to in sections 2 and 3 - Europe

R11- Highly flammable.

R36- Irritating to eyes.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapors may cause drowsiness and dizziness.

R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The information in this Safety Data Sheet is required pursuant to Annex II to Regulation (EC) No 1907/2006.

Date of issue/Date of revision : 29.09.2011.

revision

Version : 3

☑ Indicates information that has changed from previously issued version.

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.